Angenieux WIDE ANGLE Zoom
ENG lens 12x5.3 **AIF** HR

Ref. : T12x5.3 BESMD HR, T12x5.3 BESSD HR,
T12x5.3 BESSDE HR, T12x5.3 BCSMD HR,
T12x5.3 BCSSD HR, T12x5.3 BCSSDE HR,

Zoom ratio :	12x	
Focal length :	5.3 - 64 mm	10.6 - 128 mm (with 2x)
Aperture :	f/1.7 (5.3 - 36 mm)	f/3.4 (10.6 - 72 mm) (with 2x)
	f/2.6 (64 mm)	f/5.2 (128 mm) (with 2x)
MOD :	0.3 m - 1'	
Macro :	10 mm	
Extender :	2x	

SMD : Version with Standard Digital Servo control
SSD : Version with built in servo focus
SSDE : Version with 16Bits serial Digital connection for zoom & focus

Digital servo control :

> Memorized focus and zoom positions.
> Repeatable focus and zoom positions (anti backlash system).
> Auto cruise zoom function.
> Zoom limit function.
> Digital laws for focus and zoom.
> Assisted internal focus.
> Serial communication.
> Optional built in focus (SSD version).
> Optional 16 bits output optical encoder (SSDE version).

Front diam. :	92 mm
Weight (approx.) :	1.64 kg - 36 lbs
Length :	248 mm
UV filter included :	M105 x 1 in sunshade

Aspect ratio (2/3" video)	4/3 aspect ratio (8.8x6.6 mm)				16/9 aspect ratio (9.6x5.4 mm)			
Focal Length	5.3 mm	64 mm	10.6 mm (2x)	128 mm (2x)	5.3 mm	64 mm	10.6 mm (2x)	128 mm (2x)
Horizontal angular field of view	79.4°	7.8°	45°	3.9°	84.3°	8.5°	48.7°	4.3°
Object dimensions at MOD (mm)	517x387	45x34	254x190	23x17	561x313	47x27	280x156	23x13